

ULTRA MARK ASH

TECHNICAL DATA SHEET

PF	RODUCT NUMBER	DESCRIPTION	
	M280-2001	ULTRA MARK ASH	

PRODUCT DESCRIPTION:

N/A

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	N/A
Color	N/A
Sheen	N/A
Viscosity	N/A
WPG	8.997264195 lbs/gal
Solids by Volume	20.555628247 ±1%
Solids by Weight	40.027632854 ±1%
Flash Point	55.400000000 °F
HMIS	H: 2, F: 3, R: 0, P: X
Coating VOC (g/I)	645.805332029 g/l
Coating VOC (Lb/Gal)	5.389525913 lbs/gal
Material VOC (g/l)	644.402334592 g/l
Material VOC (Lb/Gal)	5.377817290 lbs/gal
#VOC/#Solid	1.493260792 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.008303151
Spread Rate	329.712277082 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	36 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	N/A

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Wood Finishes Group, Inc.; P.O. Box 22000 Hickory, NC 28603; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.