

ULTRA MARK MOCHA

TECHNICAL DATA SHEET

PRODUCT NUMBER

DESCRIPTION

M280-4033

ULTRA MARK MOCHA

PRODUCT DESCRIPTION:

N/A

PHYSICAL PROPERTIES AND SPECIFICATIONS

Color brown Sheen N/A Viscosity N/A WPG 7.641777245 lbs/gal Solids by Volume 14.355559200 ±1% Solids by Weight 23.458602919 ±1% Flash Point 55.40000000 °F HMIS H: 2, F: 3, R: 0, P: X Coating VOC (g/l) 700.188361402 g/l Coating VOC (g/l) 700.188361402 g/l Coating VOC (g/l) 5.843375907 lbs/gal Material VOC (g/l) 698.547433153 g/l Material VOC (g/l) 698.547433153 g/l Material VOC (g/l) 5.829681648 lbs/gal #VOC/#Solid 3.251983407 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.028271016 Spread Rate 230.263169568 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Technology	pigmented marker
Viscosity N/A WPG 7.641777245 lbs/gal Solids by Volume 14.355559200 ±1% Solids by Weight 23.458602919 ±1% Flash Point 55.40000000 °F HMIS H: 2, F: 3, R: 0, P: X Coating VOC (g/l) 700.188361402 g/l Coating VOC (g/l) 5.843375907 lbs/gal Material VOC (g/l) 5.843375907 lbs/gal Material VOC (g/l) 5.829681648 lbs/gal #VOC/#Solid 3.251983407 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.028271016 Spread Rate 230.263169568 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A	Color	brown
WPG 7.641777245 lbs/gal Solids by Volume 14.355559200 ±1% Solids by Weight 23.458602919 ±1% Flash Point 55.40000000 °F HMIS H: 2, F: 3, R: 0, P: X Coating VOC (g/l) 700.188361402 g/l Coating VOC (g/l) 700.188361402 g/l Coating VOC (g/l) 5.843375907 lbs/gal Material VOC (g/l) 698.547433153 g/l Material VOC (g/l) 5.829681648 lbs/gal #VOC/#Solid 3.251983407 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.028271016 Spread Rate 230.263169568 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Sheen	N/A
Solids by Volume 14.355559200 ±1% Solids by Weight 23.458602919 ±1% Flash Point 55.40000000 °F HMIS H: 2, F: 3, R: 0, P: X Coating VOC (g/l) 700.188361402 g/l Coating VOC (g/l) 5.843375907 lbs/gal Material VOC (g/l) 698.547433153 g/l Material VOC (Lb/Gal) 5.829681648 lbs/gal #VOC/#Solid 3.251983407 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.028271016 Spread Rate 230.263169568 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A	Viscosity	N/A
Solids by Weight 23.458602919 ±1% Flash Point 55.40000000 °F HMIS H: 2, F: 3, R: 0, P: X Coating VOC (g/l) 700.188361402 g/l Coating VOC (Lb/Gal) 5.843375907 lbs/gal Material VOC (g/l) 698.547433153 g/l Material VOC (Lb/Gal) 5.829681648 lbs/gal #VOC/#Solid 3.251983407 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.028271016 Spread Rate 230.263169568 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A	WPG	7.641777245 lbs/gal
Flash Point 55.40000000 °F HMIS H: 2, F: 3, R: 0, P: X Coating VOC (g/l) 700.188361402 g/l Coating VOC (Lb/Gal) 5.843375907 lbs/gal Material VOC (g/l) 698.547433153 g/l Material VOC (Lb/Gal) 5.829681648 lbs/gal #VOC/#Solid 3.251983407 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.028271016 Spread Rate 230.263169568 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Solids by Volume	14.355559200 ±1%
HMIS H: 2, F: 3, R: 0, P: X Coating VOC (g/l) 700.188361402 g/l Coating VOC (Lb/Gal) 5.843375907 lbs/gal Material VOC (g/l) 698.547433153 g/l Material VOC (Lb/Gal) 5.829681648 lbs/gal #VOC/#Solid 3.251983407 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.028271016 Spread Rate 230.263169568 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Solids by Weight	23.458602919 ±1%
Coating VOC (g/l) 700.188361402 g/l Coating VOC (Lb/Gal) 5.843375907 lbs/gal Material VOC (g/l) 698.547433153 g/l Material VOC (Lb/Gal) 5.829681648 lbs/gal #VOC/#Solid 3.251983407 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.028271016 Spread Rate 230.263169568 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Flash Point	55.40000000 °F
Coating VOC (Lb/Gal)5.843375907 lbs/galMaterial VOC (g/l)698.547433153 g/lMaterial VOC (Lb/Gal)5.829681648 lbs/gal#VOC/#Solid3.251983407 lbs/lbs solidVHAP Ratio (#VHAP/#Solid)0.028271016Spread Rate230.263169568 sq. ft./gal @ 1.0 mil DFT (no loss)Catalyst/RatioN/AReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	HMIS	H: 2, F: 3, R: 0, P: X
Material VOC (g/l)698.547433153 g/lMaterial VOC (Lb/Gal)5.829681648 lbs/gal#VOC/#Solid3.251983407 lbs/lbs solidVHAP Ratio (#VHAP/#Solid)0.028271016Spread Rate230.263169568 sq. ft./gal @ 1.0 mil DFT (no loss)Catalyst/RatioN/AReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	Coating VOC (g/l)	700.188361402 g/l
Material VOC (Lb/Gal)5.829681648 lbs/gal#VOC/#Solid3.251983407 lbs/lbs solidVHAP Ratio (#VHAP/#Solid)0.028271016Spread Rate230.263169568 sq. ft./gal @ 1.0 mil DFT (no loss)Catalyst/RatioN/AReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	Coating VOC (Lb/Gal)	5.843375907 lbs/gal
#VOC/#Solid3.251983407 lbs/lbs solidVHAP Ratio (#VHAP/#Solid)0.028271016Spread Rate230.263169568 sq. ft./gal @ 1.0 mil DFT (no loss)Catalyst/RatioN/AReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	Material VOC (g/l)	698.547433153 g/l
VHAP Ratio (#VHAP/#Solid)0.028271016Spread Rate230.263169568 sq. ft./gal @ 1.0 mil DFT (no loss)Catalyst/RatioN/AReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	Material VOC (Lb/Gal)	5.829681648 lbs/gal
Spread Rate230.263169568 sq. ft./gal @ 1.0 mil DFT (no loss)Catalyst/RatioN/AReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	#VOC/#Solid	3.251983407 lbs/lbs solid
Catalyst/RatioN/AReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	VHAP Ratio (#VHAP/#Solid)	0.028271016
ReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	Spread Rate	230.263169568 sq. ft./gal @ 1.0 mil DFT (no loss)
RetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	Catalyst/Ratio	N/A
AirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	Reducer	N/A
Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Retarder	N/A
Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	AirDry	N/A
Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Oven Dry	N/A
Recoat Instruction N/A	Shelf-Life (Unopened)	36 months
	Pot-Life (Catalyzed)	N/A
PH N/A	Recoat Instruction	N/A
	PH	N/A

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Wood Finishes Group, Inc.; P.O. Box 22000 Hickory, NC 28603; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.