

Mohawk

Finishing Products, Inc.

Product Data Sheet

E-Z SEAL PEN

M295-0001

Product Description: The use of this product over a burn-in will prevent the higher gloss that shows through in very low sheen topcoat repairs.

Advantages:

1. Good lacquer holdout.
2. Dries quickly.
3. Easy to use.

Product Limitations:

1. For interior use only

Characteristics:

Weight per gallon: 6.91 ± 0.1 lbs./gal.

Flashpoint: 54° F/12c

Package Viscosity: 23 ± 1.0 second #1 Zahn cup

Dry time: Air Dry @ 72° F, 35% Relative Humidity

To touch: 5 minutes

To handle: 10 minutes

To recoat: 10 minutes

Spec. Gravity: $.830 \pm 0.01$

Boiling Range: 147 ° F/65c

Non Volatile (wt.) $8.6 \pm 0.1\%$

Coverage: 100 square feet/gallon

Package Life: 2 years

Air Quality Data: Non-Photochemically
Reactive

Volatile Organic Compounds (VOC):

Not to exceed 757 grams/liter, 6.32 lbs/gal.

Hazardous Air Pollutants: 0.45 ± 0.05 lb./
1 lb.solids

HMIS:

Health: 1

Flammability: 3

Reactivity: 0

Personal Protection: B

Specifications:

Directions: Surface should be clean and dry. Shake well before using. To start flow, press down on tip until felt is wet. Replace tip when worn.

Safety Cautions: Keep away from heat, sparks and open flame. During use and until all vapors are gone, keep area well ventilated. Avoid breathing of vapor. **USE ONLY WITH ADEQUATE VENTILATION.** Avoid contact with skin and eyes. Wash hands after using.

KEEP OUT OF REACH OF CHILDREN

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products, Inc.

4715 State Highway 30

Amsterdam, NY 12010-7417

Phone: 518-843-1380

Fax: 518-842-3551